

Akromatic 1250 Master Stream Nozzle

STYLE 5160

Designed for flows from 250 to 1250 gpm (950-4800 lpm) - At 80 psi (5.5 bar) operating pressure

-Built-in stream shaper

Features

Designed for flows from 250 to 1250 gpm (950-4800 lpm) - At 80 psi (5.5 bar) operating pressure


- Built-in stream shaper
- Pyrolite Nozzle
- Manual Pattern Control
- 250-1250 gpm (950-4800 lpm) flow; 250 - 1000 gpm (950-3800 lpm) optional flow
- 2 1/2" or 3 1/2" (65 or 89 mm) Inlet
- No Teeth
- 9 1/2" (241 mm) Long
- 12 lbs. (26.8 kg)

Applications/Solutions

- Fire OEMs



Specifications

Type	Master Stream
Flow (GPM)	250-1250 GPM
Flow (LPM)	950-4800 LPM
Swivel Inlet	2.5" or 3.5" (65 or 89 mm)
Weight	12 lbs (5.4 kg)
Length	9 1/2" (241 mm)
Warranty	
Material	Pyrolite
Country of Manufacture	

Akromatic 1250 Master Stream Nozzle

STYLE 5160

Akromatic 1250 Master Stream Nozzle Specifications

Combination fog and straight stream master stream nozzle with automatic flow mechanism that provides a flow range of either 250 to 1000 gpm or 250 to 1250 gpm at 80 psi. The nozzle shall be constructed of durable, lightweight Pyrolite.